

N-SERIES

Specification Sheet

NMR 250 CREW AMT



www.isuzu.co.za f t

ISUZU

With you, for the long run

MODEL	NMR 250 CREW AMT
AXLE LAYOUT	4X2
CONTROL	FORWARD
MASS	
Permissible Body + Payload (kg)	2920
Tare - Total (T) (kg)	2280
Tare - Front (kg)	1520
Tare - Rear (kg)	760
GVM (kg)	5200
V (kg)	5200
GCM (kg)	8700
D/T (kg)	8700
Axle - Front GA/GAU (kg)	2900
Axle - Front A/AU (kg)	2300
Axle - Rear GA/GAU (kg)	5000
Axle - Rear A/AU (kg)	4480
Litres of Fuel Tank 1 Included in Tare (litres)	15
Litres of Fuel Tank 2 Included in Tare (litres)	0
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes
PERFORMANCE	
Gradeability at V (%)	43
Gradeability at D/T (%)	26
Max. Geared Road Speed (km/h)	118
MAJOR DIMENSIONS	
OL - Overall Length (mm)	6020
OW - Overall Width (mm)	1770
WB - Wheelbase (mm)	3345
CA - Cab to Bogie/Rear Axle (mm)	1771
CE - Cab to End of Chassis (mm)	3346
OH - Overall Height (mm)	2220
FOH - Front Overhang (mm)	1105
ROH - Rear Overhang (mm)	1455
EH - Chassis Rear End Height (mm)	810
HH - Ground Clearance (mm)	210

MODEL	NMR 250 CREW AMT
AXLE LAYOUT	4X2
CONTROL	FORWARD
MAJOR DIMENSIONS	
Chassis Width - Rear (mm)	700
Turning Radius - Curb to Curb (mm)	7250
Turning Radius - Wall to Wall (mm)	7950
ENGINE	
Make	Isuzu
Model	4JJ1-TC
Capacity (cm ³)	2999
Layout	Diesel Inline 4
Type	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	96 @ 2800
Torque @ r/min (Nm)	330 @ 1600 - 2600
Emissions Standard	Euro 3
CLUTCH	
Make	N/A
Model	N/A
Type	N/A
Diameter (mm)	N/A
Operation	Automated Hydraulic-Controlled Wet Clutch
TRANSMISSION	
Make	Isuzu
Model	MY6S (AMT)
Type	6-Speed Synchronesh
Shift	Automated Manual
No. of Gears Forward	6
First Gear Ratio : 1	5.979
Top Gear Ratio : 1	0.759
Transfer Case	No
PTO (Power Take-Off)	Optional
DRIVE AXLE	
Make	Isuzu
Model Axle Front	F029

MODEL	NMR 250 CREW AMT
AXLE LAYOUT	4X2
CONTROL	FORWARD
DRIVE AXLE	
Model Drive Axle Rear	R050
Reduction Type	Single
Final Ratio : 1	5.375
SUSPENSION	
Front	Semi-Elliptic Springs
Rear	Semi-Elliptic Springs
Shock Absorbers	Front & Rear
Stabilisers	Yes
STEERING	
Operation	Power
BRAKES	
System Type	Vacuum Hydraulic
Front	Discs
Rear	Drums
Anti-Lock Braking System (ABS)	Standard
Park / Emergency System	Drum on Propshaft
Exhaust Brake	Standard
ELECTRICAL & FUEL	
Fuel Tank 1 Capacity (litres)	100
Fuel Tank 2 Capacity (litres)	0
TYRES	
Size & Ply Rating - Front	7.00 R16-10PR (205 / 75 R16)
Size & Ply Rating - Rear	7.00 R16-10PR (205 / 75 R16)
CAB & EXTRAS	
Type	Crew
Roof	Low
No. of Bunks	0
No. of Seats (Lap Rear & Centre)	6
Air-Conditioning	Optional
Radio	Optional
Tilt Cab	No

The information above is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. Model/s shown may differ. E&OE. Date of print January 2018.